

CeilingVIEW HD-18

The CeilingVIEW HD-18 is a high definition, ceiling-mounted document camera based on a 1.3 megapixel CCD image sensor. Select from 720p, 1080i or 1080p video. With an 18x optical zoom lens, and greater light sensitivity from the CCD image sensor, CeilingVIEW HD-18 works well in locations with high ceilings and low-light situations.



CeilingVIEW HD-18
North America
999-6955-000
International
999-6955-001

FEATURES

- Component HD at 1080p, 1080i or 720p and Analog RGB
- 1/3-inch, 1.3 megapixel CCD Image Device
- 18x optical zoom lens
- Quick-Connect SR, up to 100 feet over two Cat. 5 cables
- Laser light locator for document positioning
- Metal enclosure with tile support braces and trim ring
- Includes PowerRite power supply, IR remote and EZ Control adapter

CeilingVIEW HD-18 CCU

CeilingVIEW HD-18 CCU enables you to adjust red and blue gain, pedestal, detail, iris, gamma, chroma and knee with the turn of a knob. In addition, there are two Scene Store buttons, allowing users to save specific color-matched images. Match color-critical documents for those applications where color accuracy is a must.



CeilingVIEW HD-18 CCU
North America
999-6956-000
International
999-6956-000

FEATURES

- Red and blue gain, pedestal, detail, iris, gamma, chroma and knee adjustments

CeilingVIEW HD

The CeilingVIEW HD is a high definition ceiling-mounted document system based on a megapixel native HD imaging sensor capable of 1920 x 1080 at 1080i or 1280 x 720 and 720p.

CeilingVIEW HD uses HSDS, allowing the integrator to run power, video and camera control on Cat. 5 cabling up to 400 feet.



CeilingVIEW HD
North America
999-3008-000
International
999-3008-001

FEATURES

- 2.1 megapixel HD imaging sensor (1080i or 720p)
- 10x Lens
- YPbPr or Y/C and composite video output
- Metal back box enclosure with tile support braces and trim ring
- Laser light locator for document positioning
- Quick-Connect CeilingVIEW HD/SD interface
- Includes PowerRite power supply, IR Remote and EZCamera Control Adapter

CeilingVIEW HD CCU

CeilingVIEW HD CCU enables you to adjust iris, gain, color and detail with the turn of a knob. In addition, there are two Scene Store buttons, allowing users to save specific color-matched images. Match color-critical documents for those applications where color accuracy is a must.



CeilingVIEW HD CCU
North America
999-3009-000
International
999-3009-001

FEATURES

- Red and blue gain, aperture, iris and gain controls

CeilingVIEW HD-18 DVI/HDMI

The CeilingVIEW HD-18 DVI/HDMI is built around the ClearVIEW CCU HD-18 high definition pan/tilt/zoom camera, with a 1/3-inch, 1.3 megapixel CCD imaging sensor, a glass multi-element wide dynamic zoom lens (18x optical), a tally light and a 1.8-lux rating, providing superior images in a wide range of high-definition video applications.

The CeilingVIEW HD-18 DVI/HDMI delivers simultaneous analog component video (YPbPr) and digital video (DVI-D or HDMI) outputs on separate connectors, ideal for multiple monitoring and large projection systems.



CeilingVIEW HD-18 DVI/HDMI
North America
999-6957-000
International
999-6957-001

FEATURES

- 1/3-inch CCD, 1.3 Megapixel imaging sensor
- 18x lens, Simultaneous Component HD and DV-D or HDMI outputs (up to 1080p)
- Metal enclosure with tile support braces and trim ring
- Laser light locator for document positioning
- Quick-Connect CeilingVIEW HD-18 DVI/HDMI interface
- Includes PowerRite power supply, IR Remote and EZCamera Control Adapter

CeilingVIEW SD

The CeilingVIEW SD is a standard definition ceiling-mounted document system equipped with a high-resolution 1/4-inch color CCD camera with a 36x optical zoom lens. The camera has VISCA camera control capabilities allowing control via codecs and other VISCA-based control systems.



CeilingVIEW SD NTSC
999-2008-000
PAL
999-2008-001

CeilingVIEW SD uses HSDS, allowing the integrator to run power, video and camera control on Cat. 5 cabling up to 400 feet.

FEATURES

- 1/4-inch Color CCD Image Device
- 36x Lens
- Y/C and composite output
- Metal back box enclosure with tile support braces and trim ring
- Laser light locator for document positioning
- Quick-Connect CeilingVIEW HD/SD interface
- Includes PowerRite power supply, IR Remote and EZCamera Control Adapter
- Compatible with Polycom and TANDBERG IR remotes (zoom)

CeilingVIEW SD CCU

CeilingVIEW SD CCU enables the adjustment of color, gain and iris functions on the camera with the turn of a knob. User-defined adjustments may be stored using two Scene buttons. Match color-critical documents for those applications where color accuracy is a must.



CeilingVIEW SD CCU
North America
999-2009-000
International
999-2009-001

FEATURES

- Red and blue gain, aperture, iris and gain controls